

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

Accessories (Wall sleeve is required)

WSE Wall Sleeve	Qty	
AG Architectural Grille	Qty	
DK Drain Kit	Qty	
IDK Internal Drain Kit	Qty	
BAK Baffle Adapter Kit	Qty	



Chassis requires WSE sleeve (sold and shipped separately)

Comfort & Convenience

- Convenient control from your smartphone or computer via FriedrichConnect® app
- Amazon Alexa compatible
- 24 hour programmable timer
- Smart Fan auto-adjusts fan speed to maintain desired temperature
- 3 speed fan
- Washable, antimicrobial filter
- Auto restart
- Electronic defrost control
- Insect barrier
- Reversible louver a second airflow option

Quietmaster® technology

- Steel inner wall and extra dense insulation materials block outdoor noise
- Vibration isolating design and components diminish traditional operating sound levels
- Precision engineering maximizes air flow while delivering ultra quiet operation

Energy Management & Compliance

- Convenient control from your smartphone or computer via FriedrichConnect® app
- Advanced grouping of multiple units
- Autofan mode saves money by conserving energy
- ENERGY STAR® qualified models, including heat pumps
- Environmentally-friendly R-410A refrigerant used in all models
- Recyclable packaging

Durability & Quality

- Rotary compressors provide quiet, dependable performance
- Premium stamped exterior grille
- Rifled copper tubing
- Impact resistant front cover
- High tech fins with sine wave lanced louvers increase energy efficiency by increasing surface area for heat exchange

Installation Features

- Mounts flush with the exterior wall for a neat appearance
- Ideal for thicker wall installations, where side fins don't fit
- A high efficiency replacement for 27" sleeves including Fedders A and B*. Sleeve measures 27" W x 16 3/4" H

Accessories

- WSE sleeve, ships with inside and outside weather panel and standard grille
- AG architectural grille for use with WSE sleeve
- Baffle adapter kit for use with deep sleeve installations
- Drain kit for condensate disposal
- Internal drain kit for new construction applications where condensate drain system is built-in

Wallmaster® Thru-the-wall Air Conditioners, Heat Pumps & Electric Heat models

FITS EXISTING FEDDERS SLEEVES.

Sleeve Dimensions	Friedrich WSE Sleeve	Fedders A Sleeve	Fedders B Sleeve
Height (inches)	16 3/4	16 3/4	16 3/4
Width (inches)	27	27	27
Depth (inches)	16 3/4	16 3/4	19 3/4

CHASSIS DIMENSIONS

	Height	Width	Depth	Height of Front	Width of Front	Depth with Front	Minimum Extension Into Room with Front
Chassis	15 3/4"	26 1/2"	16 1/4"	17 1/4"	27 1/2"	23 1/4"	7 1/2"

WSE SLEEVE DIMENSIONS

Model	Height	Width	Depth	Depth with Front	Minimum Extension Outside	Thru-the-wall Finished Hole		
						Height	Width	Max. Depth
WSE Sleeve	16 3/4"	27"	16 3/4"	24 1/4"	9/16"	17 1/4"	27 1/4"	15 5/16"

Chassis requires WSE sleeve (sold and shipped separately)

WallMaster® Optional Installation Accessories

WSE WALL SLEEVE

Standard Grille

Premium, stamped galvanized steel grille with powder coat paint. Ships with sleeve. Galvanized steel inner and outer weather panels also ship with sleeve.



AG, Optional Architectural Grille

Premium brushed aluminum grille




IMPORTANT:


Operating the air conditioner with incorrect rear grille or without Baffle Adapter Kit (on 19 3/4" deep sleeve) will recirculate discharge air and cause compressor overload to trip.

This will cause the unit to shut down temporarily and may lead to premature compressor failure.

CORRECT Vertical Louvers



INCORRECT Horizontal Louvers



DK / Drain Kit

Installed at the back of the unit and allows for attachment to condensate disposal system, if necessary or desired.



IDK/ Internal Drain Kit

New construction applications where a condensate drain system has been built into the wall interior.



BAK / Baffle Adapter Kit

Necessary when installing in a sleeve deeper than 16 3/4" deep, such as Fedders B sleeve (19 3/4" deep).



SPECIFICATIONS

★ ENERGY STAR® models

Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	Heating Watts	Heating Amps	EER	CEER	Estimated Yearly Energy Cost	COP	Moisture Removal Pints per Hr.	CFM	Wt Lbs Net./Ship
Cooling Only															
★ WCT08A10A	724587436655	8000	—	115	6.3	748	—	—	10.7	10.7	\$67	—	1.8	250	93/97
★ WCT10A10A	724587436662	9800	—	115	9.1	935	—	—	10.7	10.7	\$83	—	2.4	250	103/107
★ WCT12A10A	724587436952	12000	—	115	4.4	935	—	—	10.7	10.7	\$84	—	2.7	260	101/105
★ WCT10A30A	724587436945	10000	—	230	10.8	1224	—	—	9.8	9.8	\$110	—	3.5	295	112/116
★ WCT12A30A	724587436969	12000	—	230	5.5	1224	—	—	9.8	9.8	\$110	—	3.5	290	109/113
WCT16A30A	724587436976	15500	—	230	6.7	1543	—	—	9.4	9.4	\$140	—	4.8	290	119/123
Cooling with Heat Pump															
WHT12A33A	724587436983	11300	8900	230	5.5	1215	1119	5.0	9.4	9.4	\$102	2.3	3.4	275	111/115
Cooling with Electric Heat															
WET10A33A	724587436990	10000	11000	230	4.5	1020	3550	16.0	9.8	9.8	\$92	—	1.5	260	104/108
WET12A33A	724587437003	12000	11000	230	5.5	1224	3550	16.0	9.8	9.8	\$110	—	3.5	290	107/111
WET16A33A	724587437010	15500	11000	230	6.7	1543	3550	16.0	9.4	9.4	\$140	—	4.8	290	119/123

Heat Pump heating information indicates heat pump heating performance. Electric Heat heating information indicates electric heat strip performance. For Heat Pump electric heating performance refer to corresponding Electric Heat model.

HEATING PERFORMANCE: Change-over from heat pump operation to resistance operation on models indicated is automatic at a preset outside ambient temperature of approximately 35°F.

Calculate the heat loss of the space to be heated. As long as the heat loss does not exceed the resistance heating capacity rating of the unit, the heating performance will be satisfactory.

Note: all models will produce condensate. If condensate disposal is desired, an optional drain kit is available.

DEFROST CONTROL: Initiated at 30°F (outdoor coil temperature) and terminated at 43°F (outdoor coil temperature). During defrost, the compressor stops and the electric heat starts, then operates with the fan to maintain indoor comfort. Below 43°F, the unit remains in electric heat mode.

DEFROST DRAIN: Drain automatically opens at approximately 50°F to prevent condensate from freezing inside drain pan.

PLUG FACE/CIRCUIT RATING

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
WCT08A10A, WCT10A10A and WCT10A30A.	125V - 15A	5 - 15P	6	
WCT12A10A, WCT12A30A and WCT16A30A.	250V - 15A	6 - 15P	6	
WHT12A33A, WET10A33A and WET12A33A. WET15A33A.	250V - 20A	6 - 20P	6	

Model	Carton Dimensions Inches		
	Height	Width	Depth
WallMaster®			
WSE Sleeve	18"	27 1/4"	18"
Chassis	19 3/8"	30 5/8"	27 1/2"

Power cords are located on front left of WallMaster models.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models meet the ENERGY STAR® guidelines for energy efficiency.

EER is the unit's Energy Efficiency Ratio; CEER is the unit's Combined Energy Efficiency Ratio.

Your energy costs will depend on your utility rates and use. The estimated energy cost is based on a electricity cost of \$.12 per kWh.

For more information, visit www.ftc.gov/energy.

