

FRIEDRICH

ZoneAire® Premier Series PTACS
Cooling with Electric Heat, Heat Pumps

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING Btu	VOLTAGE	FRIEDRICH MODEL

Accessories

PDXWSA	Wall Sleeve	Qty		PXSB23030	Electrical Subbase - 230V 30A	Qty	
PDXWSEZ	Wall Sleeve	Qty		PXSB26515	Electrical Subase - 265V 15A	Qty	
PDXWSEXT18	Deep Wall Sleeve- For walls up to 17 1/2" deep	Qty		PXSB26520	Electrical Subbase - 265V 20A	Qty	
PDXWSEXT24	Deep Wall Sleeve- For walls up to 23 1/2" deep	Qty		PXSB26530	Electrical Subbase - 265V 30A	Qty	
PDXWSEXT	Custom Deep Wall Sleeve, For walls from 13 1/4" to 25 1/2" deep	Qty		RT7	Wired Digital Thermostat	Qty	
PXGA	Standard Outdoor Louver	Qty		RT7P	Wired Programmable Digital Thermostat	Qty	
PXAA	Architectural Louver, clear	Qty		EMRTA4	Wired Thermostat with Occupancy Sensor (white)	Qty	
PXBG	Architectural Louver, beige	Qty		EMRTB4	Wired Thermostat with Occupancy Sensor (black)	Qty	
PXSC	Architectural Louver, color matched	Qty		EMWRTA4	Wireless Thermostat with Occupancy Sensor (white)	Qty	
PDXRTA	Remote Thermostat Escutcheon Kit	Qty		EMWRTB4	Wireless Thermostat with Occupancy Sensor (black)	Qty	
PXDR10	Condensate Drain Kit (pkg/10)	Qty		WRT2	Wireless Digital Thermostat	Qty	
PXSBA	Sub Base	Qty		EMOCT	Online Connection Kit	Qty	
PXCJA	Conduit Kit w/ Junction Box	Qty		EMRAF	Remote Access Fee	Qty	
PDXDAA	Lateral Duct Adapter	Qty		EMRHCF	Energy Management Remote Humidity Control Fee	Qty	
PDXDEA	Lateral Duct Extension	Qty		PXPC23015A	LCDI 230V 15A Cord - 2.5 kW	Qty	
PXFTA	Replacement Filters (Set of 10)	Qty		PXPC23020A	LCDI 230V 205A Cord - 3.5 kW	Qty	
APWM1	FreshAire® Purification iWaves Series M	Qty		PXPC23030A	LCDI 230V 30A Cord - 5.0 kW	Qty	
PXSB23020	Electrical Subbase - 230V 15A and 20A	Qty		PXPC26515A	Non-LCDI 265V 15A Cord - 2.5 kW	Qty	
				PXPC26520A	Non-LCDI 265V 20A Cord - 3.5 kW	Qty	
				PXPC26530	Non-LCDI 265V 30A Cord - 5.0 kW	Qty	

Features

- Constant room comfort monitoring
"Instant Heat" heat pump mode quickly heats a room to the desired temperature for increased comfort
Even heat monitoring checks room temperature and automatically adds heat boost if necessary
Room freeze protection- heat initiated if temperature falls to 40°F in an unoccupied room, raising temperature to 46°F
- Dual motors for quiet operation
Durable, powder coat paint finish
Indoor coil frost sensor protects the compressor to lengthen the life of the unit.
Separate heat and cool range limits
Central desk control ready allowing hotel owners to control units from a central location
2-speed FreshAire fan

- RS-385 Communication port
Condensate removal systems uses slinger ring technology
Electronic defrost control ensures more run time in the efficient heat pump mode
Washable, easy access air filters
Service error code memory storage
Emergency heat override

ZoneAire® Premier PTAC

SPECIFICATIONS

ELECTRIC HEAT MODELS, R-32 REFRIGERANT

Models ending in 'K' are 230/208V, models ending in 'R' are 265V

Model	PDE07K3SGR3	PDE07R3SGR3	PDE09K3SGR3	PDE09R3SGR3	PDE12K3SGR3	PDE12R3SGR3	PDE15K5SGR3	PDE15R5SGR3
PERFORMANCE DATA								
Cooling Btu	7,400/7,200	7,500	10,200/9,900	10,000	12,300/12,100	12,300	14,700/14,400	14,800
Cooling Watts	560/540	560	810/790	800	1,060/1,020	1,060	1,420/1,380	1,400
Energy Efficiency Ratio, EER	13.0/13.0	13.3	12.5/12.5	12.5	11.6/11.8	11.6	10.4/10.6	10.6
Heater Size (kW)	3.5	3.5	3.5	3.5	3.5	3.5	5	5
Moisture Removal (pints/hr.)	1.69	1.69	2.11	2.11	2.74	2.74	3.17	3.17
Sensible Heat Ratio	86%	86%	85%	85%	75%	75%	67%	67%
ELECTRICAL DATA								
Voltage (1 Phase, 60 Hz)	230/208	265	230/208	265	230/208	265	230/208	265
Volt Range	253 – 187	292 – 239	253 – 187	292 – 239	253 – 187	292 – 239	253 – 187	292 – 239
Current (Amps)	2.4/2.6	2.1	3.6/3.9	3.2	4.7/5.0	4.0	6.0/6.5	5.3
Electric Heater (Amps)	15.0	13.1	15.0	13.1	15.0	13.1	21.8	18.9
Power Factor	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Compressor LRA	13.0	12.0	17.0	15.0	30.0	21.0	35.2	26.0
Compressor RLA	2.16	2.2	3.1	3.4	4.0	3.3	5.0	6.4
Outdoor Fan Motor, HP	0.080	0.080	0.080	0.080	0.086	0.086	0.086	0.086
AIRFLOW DATA								
Indoor CFM, HIGH	311.9	311.9	330	330	341.33	341.33	341	341.33
Indoor CFM, LOW	282.48	282.48	282	282	306.02	306.02	306	306.02
Vent CFM	75	75	75	75	75	75	75	75
PHYSICAL DATA								
Sleeve Dimensions (H x W x D)	16" x 42" x 13 3/4" (all models)							
Dimensions with Front (H x W x D)	16" x 42" x 21 1/2" (all models)							
Cut Out Dimensions (H x W x D)	16 1/4" x 42 1/4" (all models)							
Net Weight (lbs.)	110.25	110.25	110.3	110.3	114.66	114.66	114.7	114.7
Shipping Weight (lbs.)	132.3	132.3	132.3	132.3	136.71	136.71	136.7	136.7
R-32 Charge (oz.)	17.64	17.64	17.28	17.28	21.16	21.16	19.75	19.79
Dimensions with Packaging (inches)	17 7/8" x 45" x 25 1/4" (all models)							

		230/208V ELECTRIC HEATER RATING (CONFIGURATION BASED ON POWER CORD)			
POWER CORD #	VOLTAGE	BRANCH CKT AMPS	MCA	WATTS	
PXPC23015A	230/208	15	13.9	2,500	
PXPC23020A	230/208	20	19.9	3,500	
PXPC23030A	230/208	30	27.5	5,000	
PXPC26515A	265V	15	12.0	2,500	
PXPC26520A	265V	20	16.8	3,500	
PXPC26530	265V	20	23.8	5,000	

Receptacles and Fuse Types						
Voltage	230V			265V		
Heater Size	2.5 kW	3.5 kW	5.0 kW	2.5 kW	3.5 kW	5.0 kW
Receptacles						
NEMA# Receptacle	6-15R	6-20R	6-30R	7-15R	7-20R	7-30R
NEMA# Plug	6-15P	6-20P	6-30P	7-15P	7-20P	7-30P

Standard power cord installed on each unit (7-12kW-3.5KW), (15K-5.0 KW)
Optional 2.5Kw, 3.5Kw or 5kW through universal heater cord selection

Due to continuing research in new energy-saving technology, specifications are subject to change without notice. Warranty limited to installations in the United States, Puerto Rico, Mexico and Canada only. See warranty documentation for full details



ZoneAire® Premier PTAC

SPECIFICATIONS

HEAT PUMP MODELS, R-32 REFRIGERANT

Models ending in 'K' are 230/208V, models ending in 'R' are 265V

Model	PDH07K3SGR3	PDH07R3SGR3	PDH09K3SGR3	PDH09R3SGR3	PDH12K3SGR3	PDH12R3SGR3	PDH15K5SGR3	PDH15R5SGR3
PERFORMANCE DATA								
Cooling Btu	7,400/7,200	7,300	9,700/9,400	9,800	12,100/11,900	12,000	14,600/14,200	14,500
Cooling Watts	570/560	560	800/780	810	1,040/1,000	1,030	1,400/1,360	1,390
Energy Efficiency Ratio, EER	13.0/13.0	13.0	12.1/12.1	12.1	11.6/11.8	11.6	10.4/10.4	10.4
Heater Size (kW)	3.5	3.5	3.5	3.5	3.5	3.5	5	5
Reverse Heating Btu	6,000/5,800	6,000	8,500/8,200	8,600	10,900/10,700	10,700	13,800/13,300	13,300
Heating Watts	490/460	490	690/670	690	940/900	920	1,310/1,250	1,250
COP (W/W)	3.6/3.6	3.6	3.6/3.6	3.65	3.4/3.46	3.4	3.1/3.1	3.1
Moisture Removal (pints/hr.)	1.69	1.69	2.11	2.11	2.75	2.75	3.17	3.17
Sensible Heat Ratio	83/80%	83%	75%	75%	70%	70%	---	---
ELECTRICAL DATA								
Voltage (1 PHASE, 60 Hz)	230/208	265	230/208	265	230/208	265	230/208	265
Volt Range	253-187.2	238.5-291.5	253-187	292-239	253-187	292-239	253-187	292-239
Current (Amps)	2.4/2.6	2.1	3.6/3.9	3.1	4.6/4.9	4	6.0/6.5	5.3
Electric Heater (Amps)	15.0	13.1	15.0	13.1	15.0	13.1	21.8	18.9
Reverse Heat (Amps)	2.1/2.3	1.8	3.1/3.2	2.6	4.1/4.3	3.5	5.6/5.9	4.7
Power Factor	0.99/1.0	1.0	0.99	0.99	0.99	0.99	---	---
Compressor LRA	13	12	17	15	30	21	35.2	26
Compressor RLA	2.16	2.2	3.1	3.4	4.0	4.5	5	6.4
Outdoor Fan Motor, HP	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08
AIRFLOW DATA								
Indoor CFM, HIGH	311.9	311.9	330	330	340	341	341	341
Indoor CFM, LOW	282.48	282.48	282	282	306	306	306	306
Outdoor Air	75	75	52	52	52	52	75	75
PHYSICAL DATA								
Sleeve Dimensions (H x W x D)	16" x 42" x 13 3/4" (all models)							
Dimensions with front (H x W x D)	16" x 42" x 21" (all models)							
Cut Out Dimensions (H x W)	16 1/4" x 42 1/4" (all models)							
Net Weight (lbs.)	112.45	112.45	115	115	119	119	120	120
Shipping Weight (lbs.)	134.5	134.5	135	135	141	141	142	142
R-32 Charge (oz.)	27.51	27.51	24.7	24.7	20.92	28.9	29.63	28.57
Dimensions with Packaging (inches)	17 7/8" x 45" x 25 1/4" (all models)							

		230/208V ELECTRIC HEATER RATING		
		(CONFIGURATION BASED ON POWER CORD)		
POWER CORD #	VOLTAGE	BRANCH CKT AMPS	MCA	WATTS
PXPC23015A	230/208	15	13.9	2,500
PXPC23020A	230/208	20	19.9	3,500
PXPC23030A	230/208	30	27.5	5,000
PXPC26515A	265V	15	12.0	2,500
PXPC26520A	265V	20	16.8	3,500
PXPC26530	265V	20	23.8	5,000

Receptacles and Fuse Types						
Voltage	230V			265V		
Heater Size	2.5 kW	3.5 kW	5.0 kW	2.5 kW	3.5 kW	5.0 kW
Receptacles						
NEMA# Receptacle	6-15R	6-20R	6-30R	7-15R	7-20R	7-30R
NEMA# Plug	6-15P	6-20P	6-30P	7-15P	7-20P	7-30P

Standard power cord installed on each unit (7-12k-3.5KW), (15K-5.0 KW)
Optional 2.5Kw, 3.5Kw or 5kW through universal heater cord selection

Due to continuing research in new energy-saving technology, specifications are subject to change without notice. Warranty limited to installations in the United States, Puerto Rico, Mexico and Canada only. See warranty documentation for full details



Friedrich Air Conditioning Co. | Friedrich.com

PTAC ZONEAIRE PREMIER SERIES SUBMITTAL (REV 09-11-25)

